

View Online at <https://aerobasegroup.com/nsn/5306-00-413-6250>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.813 inches and 0.875 inches

Fastener Length:

Between 1.813 inches and 1.875 inches

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

First Diameter From Head:

0.164 inches

Second Diameter From Head:

Between 0.105 inches and 0.115 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.047 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.000 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

63.0 microinches

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0