

View Online at <https://aerobasegroup.com/nsn/5306-00-413-6625>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.125 inches and 1.185 inches

**Fastener Length:**

5.375 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.490 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Extended Washer Diameter:**

0.688 inches

**Extended Washer Thickness:**

Between 0.110 inches and 0.120 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 4.190 inches and 4.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0