NSN 5306-00-415-6102

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-415-6102 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.357 inches and 0.439 inches **Fastener Length:** Between 5.664 inches and 5.684 inches **Head Style:** Dished hexagon **Head Height:** Between 0.189 inches and 0.204 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3733 inches and 0.3742 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 5.125 inches and 5.141 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 36.0 rockwell c and 41.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 5.549 inches first hole and 5.579 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** W/retaining element on shank Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5306-00-415-6102Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A003b0