

View Online at <https://aerobasegroup.com/nsn/5306-00-415-7042>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

2.500 inches

Fastener Length:

11.250 inches

Head Style:

Pan no. 2

Head Diameter:

Between 2.716 inches and 2.722 inches

Head Height:

1.250 inches

Hole Diameter:

0.312 inches

Shank Unthreaded Hole Diameter:

0.125 inches first hole

First Diameter From Head:

Between 1.999 inches and 2.000 inches

Second Diameter From Head:

1.918 inches

Third Diameter From Head:

Between 1.999 inches and 2.002 inches

Fourth Diameter From Head:

1.918 inches

Fifth Diameter From Head:

Between 1.999 inches and 2.002 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

2.750 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

5.250 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

6.250 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

8.750 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

10.875 inches

Thread Diameter:

2.000 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Hardness Rating:

258.0 brinell standard

Hole Configuration Style:

Round chord

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.312 inches first hole

Externally Relieved Body Diameter Quantity:

5

Material:

Steel comp 3140

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0