## NSN 5306-00-418-2888

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-418-2888 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.690 inches and 0.705 inches **Fastener Length:** 1.320 inches **Head Style:** Hexagon extended washer **Head Height:** 0.370 inches Width Between Flats: Between 0.870 inches and 0.875 inches **Extended Washer Diameter:** 1.060 inches **Extended Washer Thickness:** 0.060 inches **Shoulder Diameter:** 0.8110 inches first shoulder and 0.8160 inches first shoulder **Shoulder Length:** 0.320 inches first shoulder **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Shoulder Shape:** Round first shoulder **Special Features:** Apply everlube 642 or equal to threads per mil-l-46010; paint one coat lustreless enamel per tt-e-527; prime screw wxcept threads color no.34084 per federal standard tt-p-1757 Color: Green Material: Steel comp 4140 **Material Specification:** 66 federal standard single material response

Shelf Life: N/a

Unc

**Surface Treatment:** Zinc and chromate

**Thread Series Designator:** 

## **NSN 5306-00-418-2888** Shoulder Bolt - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

Demilitarization:

No

Fiig:

A003b0