

View Online at <https://aerobasegroup.com/nsn/5306-00-419-9483>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.445 inches

**Fastener Length:**

1.695 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.500 inches

**Head Height:**

Between 0.115 inches and 0.125 inches

**Shank Unthreaded Hole Diameter:**

0.125 inches first hole and 0.129 inches first hole

**First Diameter From Head:**

0.312 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.250 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.383 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Shank end relieved 0.063 depth 0.680 lg. Perpendicular to the drilled hole in shank

**Material:**

Steel comp 1018 or steel comp 1035 or steel comp 1109 or steel comp 1137

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0