NSN 5306-00-419-9544

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-419-9544

2a Thread Direction: Right-hand Thread Length: 1.150 inches Fastener Length: 2.810 inches Head Style: Dee Head Diameter: 1.250 inches Head Height: 0.300 inches Distance From Centerline To Flat: 0.310 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches Shoulder Length: 0.420 inches 1.750 inches Rib Length: 0.420 inches 1.751 inches Rib Length: 0.420 inches 1.751 inches Rib Length: 0.420 inches 1.751 inches 0.420 inches Rib Longth: 0.420 inches 1.751 inches Rib Dolateer: 0.730 inches Rib Longth: 0.420 inches Rib Minor Diameter: 0.730 inches Rib Dolateet:	-	
Thread Direction: Right-hand Thread Length: 1.150 inches Fastener Length: 2.810 inches Head Style: Dee Head Direction: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.310 inches Shoulder Diameter: 0.781 inches first shoulder Rib Length: 0.420 inches Distance From Centerline To Flat: 0.310 inches Shoulder Diameter: 0.781 inches first shoulder Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Length: 0.230 inches Rib Length: 0.230 inches Rib Longth: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Monor Diameter: 0.230 inches Rib Monor Diameter: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Monor Diameter: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Length 0.230 inches Rib Length 0.230 inches <	Thread Class:	
Right-hand Thread Length: 1.150 inches Fastener Length: 2.810 inches Head Siyle: Dee Head Diameter: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.280 inches Rib Major Diameter: 0.791 inches 0.781 inches Rib Major Diameter: 0.781 inches 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.280 inches Rib Major Diameter: 0.290 inches Rib Dameter: 0.290 inches Rib Dameter: 0.292 inches Thread Diameter: 0.425 inches Thread Quy Per Inch (tpi): 18 Hardness Rating: 3.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Rib bed first shoulder	2a	
Thread Length: 1.150 inches Fastener Length: 2.810 inches Head Style: 2.810 inches Head Style: Dee Head Diameter: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.380 inches Shoulder Diameter: 0.781 inches first shoulder Rib Length: 0.420 inches Bib Length: 0.420 inches Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Rib Length: 0.440 Angle: 1.440	Thread Direction:	
1.150 inches Fastener Length: 2.810 inches Head Style: Dee Head Diameter: 1.250 inches Head Height: 0.300 inches Distance From Centerline To Flat: 0.3510 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Length: 0.420 inches Diatere From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Diates Rib Length: 0.420 inches Diates Rib Longth: 0.420 inches Diates Diates Diates Diates Diates Rib Length: 0.420 inches Rib Minor Diameter: 0.730 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 30. rockwell	Right-hand	
Fastener Length: 2.810 inches Head Style: Dee Head Diameter: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Major Diameter: 0.781 inches Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Rib Moinor Diameter: 0.420 inches Rib Moinor Diameter: 0.420 inches Rib Quantity: 1 Thread Diameter: 0.799 inches Rib Quantity: 1 Thready Up Per Inch (tpi): 18 Hardness Rating: 3.0 rockwell c Rib Included Angle: 28.0 degrees <t< td=""><td>Thread Length:</td><td></td></t<>	Thread Length:	
Alto inches Head Style: Dee Head Diameter: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.380 inches Distance From Centerline To Flat: 0.380 inches Shoulder Diameter: 0.781 inches first shoulder Rib Major Diameter: 0.420 inches first shoulder Rib Length: 0.420 inches Rib Minor Diameter: 0.420 inches Rib Major Diameter: 0.440 inches Rib Major Di	1.150 inches	
Head Style: Dee Head Diameter: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Rib Major Diameter: 0.420 inches Rib Length: 0.420 inches Distance From Largest Diameter Col Bearing Surface Of Head To Ribs: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.799 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thread Diameter: 0.625 inches Thread Diameter: 0.625 inches Thread Diameter: 0.791 Inches Rating: 0.792 Inches Bit Included Angle: 28.0 degrees Shoulder Shape: Rib Doulder Shape:	Fastener Length:	
Dee Head Diameter: 1.250 inches Head Height: 1.250 inches Head Height: 1.350 inches Distance From Centerline To Flat: 1.350 inches Shoulder Diameter: 1.751 inches first shoulder Att bage Diameter: 1.751 inches Rib Length: 1.751 inches Rib Major Diameter: 1.752 inches Rib Major Rib Rib Major Rib Major Rib	2.810 inches	
Head Diameter: 1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Bhoulder Length: 0.420 inches Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Bistance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Bistance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Bistance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Bistance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Bistance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Bib Minor Diameter: 0.420 inches Rib Duameter: 0.420 inches Rib Quantity: 1 Thread Diameter: 0.425 inches Thread Diameter: 0.425 inches Thread Vy Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Head Style:	
1.250 inches Head Height: 0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches 0.781 inches Rib Major Diameter: 0.781 inches 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.791 inches Rib Longth: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Rib Minor Diameter: 0.799 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribded first shoulder	Dee	
Head Height: 0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Bistance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.203 inches Rib Minor Diameter: 0.203 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thread Nameter: 0.625 inches Thread Nameter: 0.625 inches Thread Qty Per Inch (tpi): 18 Hardness Rating: 3.0 rockwell c Rib Included Angle: 28.0 degrees </td <td>Head Diameter:</td> <td></td>	Head Diameter:	
0.380 inches Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Length: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Rib Minor Diameter: 0.230 inches Rib Moinor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thread Diameter: 0.625 inches Thread Diameter: 0.625 inches Thread Diameter: 0.625 inches Thread Diameter: 0.625 inches Thread Vat Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	1.250 inches	
Distance From Centerline To Flat: 0.510 inches Shoulder Diameter: 0.781 inches first shoulder Rib Major Diameter: 0.420 inches first shoulder Rib Length: 0.781 inches Rib Length: 0.781 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Head Height:	
0.510 inches Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Rib Minor Diameter: 0.420 inches Rib Minor Diameter: 0.420 inches Rib Minor Diameter: 0.420 inches Rib Quantity: 1 Thread Diameter: 0.425 inches Thread Y Per Inch (tpi): 18 Hardness Rating: 3.0. rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	0.380 inches	
Shoulder Diameter: 0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Length: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Distance From Centerline To	Flat:
0.781 inches first shoulder Shoulder Length: 0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Length: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape:	0.510 inches	
Shoulder Length: 0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Rib Minor Diameter: 0.420 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 30.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape:	Shoulder Diameter:	
0.420 inches first shoulder Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.420 inches Rib Minor Diameter: 0.230 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape:	0.781 inches first shoulder	
Rib Major Diameter: 0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Quantity: 1 1 Thread Diameter: 0.625 inches Thread Piameter: 0.625 inches Thread Y Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape:	Shoulder Length:	
0.781 inches Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.230 inches Rib Quantity: 1 1 1 1 1 1 1 1 1 1 1 1 1	0.420 inches first shoulder	
Rib Length: 0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape:	Rib Major Diameter:	
0.420 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape:	0.781 inches	
Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.230 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Rib Length:	
0.230 inches Rib Minor Diameter: 0.709 inches Rib Quantity: 1 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	0.420 inches	
Rib Minor Diameter: 0.709 inches Rib Quantity: 1 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Distance From Largest Diam	eter Of Bearing Surface Of Head To Ribs:
0.709 inches Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	0.230 inches	
Rib Quantity: 1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Rib Minor Diameter:	
1 Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	0.709 inches	
Thread Diameter: 0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Rib Quantity:	
0.625 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	1	
Thready Qty Per Inch (tpi): 18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Thread Diameter:	
18 Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	0.625 inches	
Hardness Rating: 33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Thready Qty Per Inch (tpi):	
33.0 rockwell c Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	18	
Rib Included Angle: 28.0 degrees Shoulder Shape: Ribbed first shoulder	Hardness Rating:	
28.0 degrees Shoulder Shape: Ribbed first shoulder	33.0 rockwell c	
Shoulder Shape: Ribbed first shoulder	Rib Included Angle:	
Ribbed first shoulder	28.0 degrees	
	Shoulder Shape:	
Material:		
	Material:	
Steel comp 8740	Steel comp 8740	

NSN 5306-00-419-9544

Ribbed Shoulder Bolt - Page 2 of 2



Material Specification:

Qq-s-624 federal specification all material responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0