

View Online at <https://aerobasegroup.com/nsn/5306-00-424-4421>

Thread Direction:

Right-hand

Thread Length:

1.375 inches

Fastener Length:

4.688 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

1.188 inches

Head Height:

0.500 inches

Width Between Flats:

Between 0.988 inches and 0.990 inches

Shank Unthreaded Hole Diameter:

0.156 inches first hole

First Diameter From Head:

Between 0.751 inches and 0.752 inches

Second Diameter From Head:

Between 0.663 inches and 0.666 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.375 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

3.313 inches

Thread Diameter:

0.750 inches

Nonstandard Thread Pitch Diameter:

+0.7062/+0.7094 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

27.0 rockwell c and 31.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.219 inches first hole

Externally Relieved Body Diameter Quantity:

2

Special Features:

Two drilled holes in shank, 0.437 in. C to c

Material:

Steel comp 4140

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0