

View Online at <https://aerobasegroup.com/nsn/5306-00-424-4421>

**Thread Direction:**

Right-hand

**Thread Length:**

1.375 inches

**Fastener Length:**

4.688 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

1.188 inches

**Head Height:**

0.500 inches

**Width Between Flats:**

Between 0.988 inches and 0.990 inches

**Shank Unthreaded Hole Diameter:**

0.156 inches first hole

**First Diameter From Head:**

Between 0.751 inches and 0.752 inches

**Second Diameter From Head:**

Between 0.663 inches and 0.666 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.375 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

3.313 inches

**Thread Diameter:**

0.750 inches

**Nonstandard Thread Pitch Diameter:**

+0.7062/+0.7094 inches

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

27.0 rockwell c and 31.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.219 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

Two drilled holes in shank, 0.437 in. C to c

**Material:**

Steel comp 4140

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0