

View Online at <https://aerobasegroup.com/nsn/5306-00-425-8474>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.167 inches and 1.270 inches

**Fastener Length:**

Between 1.300 inches and 1.320 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

Between 0.730 inches and 0.737 inches

**Head Height:**

Between 0.060 inches and 0.070 inches

**Width Between Flats:**

Between 0.310 inches and 0.330 inches

**Shoulder Diameter:**

0.248 inches first shoulder and 0.250 inches first shoulder

**Shoulder Length:**

0.050 inches first shoulder and 0.070 inches first shoulder

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Two holes drilled through head 0.098 in. Min 0.103 in. Maximum dia, 0.520 in. C to c between bolt holes

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Pwa 37 fscm 77445 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0