Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-427-7024

Inread Class: 3a Thread Direction: Right-hand Thread Length: 0.310 inches Fastenr Length: Between 1.359 inches and 1.406 inches Head Siyle: Double hexagon whole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Sering Lyn): 22 Min. Tensile Strength (ps): 23 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Materia: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mi-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Sheff Life: Na		
Tread Direction: Right-hand Thread Length: 0.310 inches Fasteer Length: Between 1.359 inches and 1.406 inches Head Style: Double hexagon whole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Dimeter: Between 0.359 inches and 0.251 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.140 inches 11 Thready Guy Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch Hardness Rating: 1.01 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadimim Mil-reast7, type 1, class 2 military specification single treatment response Thread Stries Designato: Mil-reastis Stre	Thread Class:	
Right-hand Thread Length: 0.310 inches Fastener Length: Between 1.359 inches and 1.406 inches Head Style: Double hexagon whole Head Height: 0.214 inches With Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.359 inches Extended Washer Thickness: 0.040 inches Between 0.031 inches and 0.451 inches Between 0.035 inches and 0.459 inches Between 0.031 inches and 0.459 inches Between 0.031 inches and 0.401 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.490 inches Thread Diameter: 0.490 inches Thread Diameter: 0.490 inches Thread Surget (psi): 26 Min-Tensile Strength (psi): 260000 pounds per square inch Hardenss Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Min-Fasi1, tpsi - diase 2 military specification single treatment response		
Tread Length: 0.310 inches Fastener Length: Between 1.359 inches and 1.406 inches Head Style: Double hexagon whole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Thread Vaty Per Inch (tpi): 32 Mint-Tensile Strength (psi): 240000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Miterial: Stel comp h11 or stel comp 4340 Surface Treatment Specification: Mid-Savis, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf		
0.310 indes Fastener Length: Between 1.359 inches and 1.406 inches Head Style: Double hexagon whole Head Style: Double hexagon whole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Dimeter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Valy Per Inch (tpi): 32 Min. Tensile Strength (psi): 200000 pounds per square inch Hardiness Stele comp 1.11 or stele comp 4340 Steriel Comp 1.11 or stele comp 4340 Streiel Treatment Cadmim Streiel Streight (psi): Stele comp 1.11 or stele comp 4340 Stele comp 1.11 or stele comp 4340 Streiel Treatment Cadmim Streiel S	-	
Pastenci Length: Between 1.359 inches and 1.406 inches Head Style: Double hexagon whole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.411 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Thread Diameter 1 Between 1.049 inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body D	-	
Between 1.359 inches and 1.406 inches Head Style: Double hexagon whole Head Heigh: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.259 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thready City Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.1 orckwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Matreis: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmim Surface Treatment Specification:		
Head Style: Double hexagon whole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thread String: 0.190 inches Thread String Kromy Head 260000 pounds per square inch Hardness Rating: 200000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Extendial Kelieved Body Diameter Quantity: 1 Material: Stel comp h11 or stel comp 4340 Surface Treatment: Cadmim Material: Material: Material: Material: Stel comp h11 or stel comp 4340 Surface Treatment Specification	-	
Double hexagon w/hole Head Height: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Thread Diameter: 0.190 inches Thready Gty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2600000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Minerial: Stel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mike-a837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf		
Head Heigh: 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.400 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Gty Per Inch (tpi): 32 Min. Ensile Strength (psi): 260000 pounds per square inch Hardness Rating: 1.10 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Sterio ph 11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification Mihc-Ba37, type 1, class 2 military specification single treatment response Thread Steries Designator: Unjf	-	
0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thread y dy Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Mik-e8837, type 1, class 2 military specification single treatment response Thread Steries Designator: Unjf Shelf Life:		
Width Between Flats:Between 0.243 inches and 0.251 inchesExtended Washer Diameter:Between 0.359 inches and 0.369 inchesExtended Washer Thickness:0.040 inchesFirst Diameter From Head:Between 0.031 inches and 0.041 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.049 inches and 1.096 inchesThread Diameter:0.190 inchesThready Gty Per Inch (tpi):32Min. Tensile Strength (psi):20000 pounds per square inchHardness Rating:51.0 rockwell c and 54.0 rockwell cExternally Relieved Body Diameter Quantity:1Materiai:Stel comp h11 or stel comp 4340Surface Treatment:CadmiumMic-8837, type 1, class 2 military specification single treatment responseThread Steries Designator:UnjfShelf Life:	-	
Between 0.243 inches and 0.251 inches Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Gty Per Inch (tpi): 32 Min. Tensile Strength (psi): 20000 pounds per square inch Hardness Rating: 51.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Stele comp h11 or stel comp 4340 Surface Treatment: Cadmium Min-Creatise Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:		
Extended Washer Diameter: Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:		
Between 0.359 inches and 0.369 inches Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:		
Extended Washer Thickness: 0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:		
0.040 inches First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:		
First Diameter From Head: Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Stele comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:		
Between 0.031 inches and 0.041 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.049 inches and 1.096 inchesThread Diameter:0.190 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):260000 pounds per square inchHardness Rating:51.0 rockwell c and 54.0 rockwell cExternally Relieved Body Diameter Quantity:1Material:Steel comp h11 or steel comp 4340Surface Treatment:CadmiumMil-c-8837, type 1, class 2 military specification single treatment responseThread Series Designator:UnifSurface Treatment SpecificationMaterial:Surface Treatment SpecificationMil-c-8837, type 1, class 2 military specification single treatment responseStries Designator:UnifSurface Treatment SpecificationSurface Treatment Specification single treatment responseSurface Treatment Specification single treatment responseStries Designator:UnifSurface Treatment Specification single treatment responseStries Designator:UnifSteel Life:		
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	First Diameter From Head:	
Between 1.049 inches and 1.096 inches Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Between 0.031 inches and 0.041 inches	
Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Between 1.049 inches and 1.096 inches	
Thready Qty Per Inch (tpi):3234Min. Tensile Strength (psi):260000 pounds per square inchHardness Rating:51.0 rockwell c and 54.0 rockwell cExternally Relieved Body Diameter Quantity:1Material:Steel comp h11 or steel comp 4340Surface Treatment:CadmiumSurface Treatment Specification:Mil-c-8837, type 1, class 2 military specification single treatment responseInteread Series Designator:UnjfShelf Life:	Thread Diameter:	
32 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	0.190 inches	
Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Thready Qty Per Inch (tpi):	
260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	32	
Hardness Rating:51.0 rockwell c and 54.0 rockwell cExternally Relieved Body Diameter Quantity:1Material:Steel comp h11 or steel comp 4340Surface Treatment:CadmiumSurface Treatment Specification:Mil-c-8837, type 1, class 2 military specification single treatment responseThread Series Designator:UnjfShelf Life:	Min. Tensile Strength (psi):	
51.0 rockwell c and 54.0 rockwell c Externally Relieved Body Diameter Quantity: 1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	260000 pounds per square inch	
Externally Relieved Body Diameter Quantity:1Material:Steel comp h11 or steel comp 4340Surface Treatment:CadmiumSurface Treatment Specification:Mil-c-8837, type 1, class 2 military specification single treatment responseThread Series Designator:UnjfShelf Life:	Hardness Rating:	
1 Material: Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	51.0 rockwell c and 54.0 rockwell c	
Material:Steel comp h11 or steel comp 4340Surface Treatment:CadmiumSurface Treatment Specification:Mil-c-8837, type 1, class 2 military specification single treatment responseThread Series Designator:UnjfShelf Life:	Externally Relieved Body Diameter Quantity:	
Steel comp h11 or steel comp 4340 Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	1	
Surface Treatment: Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Material:	
Cadmium Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Steel comp h11 or steel comp 4340	
Surface Treatment Specification: Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Surface Treatment:	
Mil-c-8837, type 1, class 2 military specification single treatment response Thread Series Designator: Unjf Shelf Life:	Cadmium	
Thread Series Designator: Unjf Shelf Life:	Surface Treatment Specification:	
Unjf Shelf Life:	Mil-c-8837, type 1, class 2 military specification single treatment response	
Shelf Life:	Thread Series Designator:	
	Unjf	
N/a	Shelf Life:	
	N/a	

NSN 5306-00-427-7024

Externally Relieved Body Bolt - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.