NSN 5306-00-427-7027

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-427-7027 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.310 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.214 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.359 inches and 0.369 inches **Extended Washer Thickness:** 0.040 inches **First Diameter From Head:** Between 0.031 inches and 0.041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.424 inches and 0.456 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp h11 or steel comp 4340 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 1, class 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-00-427-7027

Externally Relieved Body Bolt - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.