

View Online at <https://aerobasegroup.com/nsn/5306-00-427-7027>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.310 inches

Fastener Length:

Between 0.734 inches and 0.766 inches

Head Style:

Double hexagon w/hole

Head Height:

0.214 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.359 inches and 0.369 inches

Extended Washer Thickness:

0.040 inches

First Diameter From Head:

Between 0.031 inches and 0.041 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.424 inches and 0.456 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp h11 or steel comp 4340

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type 1, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.