NSN 5306-00-427-8659

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-427-8659 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.375 inches and 0.470 inches **Fastener Length:** Between 0.675 inches and 0.695 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **Shoulder Diameter:** 0.195 inches first shoulder and 0.196 inches first shoulder **Shoulder Length:** 0.225 inches first shoulder and 0.245 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 175000 pounds per square inch **Hardness Rating:** 34.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 115000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Nickel alloy **Material Specification:** Ams 5708 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-00-427-8659 Shoulder Bolt - Page 2 of 2



			ure:	

Demilitarization:

No

Fiig:

A003b0