NSN 5306-00-429-3425

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-429-3425 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 1.698 inches and 1.728 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.080 inches first hole **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.525 inches first hole and 1.575 inches first hole Material: Titanium alloy uns r54520 **Material Specification:** Nas621, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas673 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-00-429-3425

Shear Bolt - Page 2 of 2



Fiig:

A003b0