NSN 5306-00-431-6651

U Bolt - Page 1 of 1

Mil-std (military Standard):

Mil-p-14553 spec.



View Online at https://aerobasegroup.com/nsn/5306-00-431-6651 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 2.500 inches **Distance From Inside Center Of Bend To Bolt End:** 12.375 inches **Inside Distance Between Shanks:** 2.562 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 28.0 rockwell c and 33.0 rockwell c Material: Steel comp 8640 or steel comp 8642 or steel comp 8645 or steel comp 4140 or steel comp 4142 or steel comp 4145 **Material Specification:** Qq-s-624 federal specification all material responses or 66 federal standard all material responses or sae assn standard all material responses **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification 1st treatment response and qq-z-325, type 2, class 3 federal specification 2nd treatment response and tt-p-636 federal specification 3rd treatment response or tt-p-664 federal specification 3rd treatment response or mil-p-14553 military specification 3rd treatment response **Style Designator:** Square bend **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A003b0