

View Online at <https://aerobasegroup.com/nsn/5306-00-431-9468>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.580 inches and 0.610 inches

Fastener Length:

3.498 inches

Head Style:

Square

Head Height:

0.250 inches

Width Between Flats:

1.476 inches

Shoulder Diameter:

0.763 inches first shoulder and 0.773 inches first shoulder

Shoulder Length:

0.580 inches first shoulder and 0.610 inches first shoulder

Hole Diameter:

Between 0.077 inches and 0.082 inches

Shank Unthreaded Hole Diameter:

0.105 inches first hole and 0.110 inches first hole

Thread Diameter:

0.875 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Hole Configuration Style:

Square longitudinal hole

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.352 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

Mil-s-6709 comp a cond e4 military standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6709 spec.