

View Online at <https://aerobasegroup.com/nsn/5306-00-432-3936>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.682 inches and 0.732 inches

Fastener Length:

Between 2.192 inches and 2.222 inches

Head Style:

Double hexagon w/hole

Head Height:

0.405 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Extended Washer Diameter:

Between 0.715 inches and 0.725 inches

Extended Washer Thickness:

0.075 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.490 inches and 1.510 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Hole Configuration Style:

Hexagon flats

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.