## NSN 5306-00-432-4139



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-432-4139 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.596 inches and 0.616 inches **Fastener Length:** 0.688 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.258 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.072 inches and 0.092 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 175000 pounds per square inch **Hardness Rating:** 34.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 115000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Ams 5708 assn standard single material response

Nickel alloy **Material Specification: Thread Series Designator:** Unjf Shelf Life: N/a

## **NSN 5306-00-432-4139** Machine Bolt - Page 2 of 2



			ıre:

Demilitarization:

No

Fiig:

A003b0