NSN 5306-00-432-4676



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-432-4676 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.401 inches and 0.421 inches Fastener Length: 0.500 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.303 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.060 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.079 inches and 0.099 inches **Hole Quantity:** 4 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 34.0 rockwell c and 44.0 rockwell c

Min. Tensile Strength (psi): 175000 pounds per square inch **Hardness Rating: Minimum Yield Strength:** 115000 pounds per square inch **Hole Configuration Style:** Hexagon flats **Surface Finish:** 32.0 microinches threads

NSN 5306-00-432-4676

Machine Bolt - Page 2 of 2



Material:
Nickel alloy
Material Specification:
Ams 5708 assn standard single material response
Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2410 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0