## NSN 5306-00-432-6091

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-432-6091 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: **Fastener Length:** 0.875 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.303 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** 0.060 inches **Hole Diameter:** 0.060 inches **Thread Diameter:** 0.250 inches **Grip Length: Hole Quantity:** 4 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 38.0 rockwell c **Minimum Yield Strength:** 120000 pounds per square inch **Hole Configuration Style:** Hexagon flats

Between 0.750 inches and 0.796 inches Between 0.079 inches and 0.125 inches **Surface Finish:** 32.0 microinches threads

## **NSN 5306-00-432-6091** Machine Bolt - Page 2 of 2



Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0