

View Online at <https://aerobasegroup.com/nsn/5306-00-432-6117>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.580 inches and 0.600 inches

**Fastener Length:**

0.688 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.338 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

0.500 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.088 inches and 0.108 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

175000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 44.0 rockwell c

**Minimum Yield Strength:**

115000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Surface Finish:**

32.0 microinches threads

**Material:**

Nickel alloy

**Material Specification:**

Ams 5708 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0