

View Online at <https://aerobasegroup.com/nsn/5306-00-437-2670>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.844 inches

Fastener Length:

Between 11.094 inches and 11.104 inches

Head Style:

Dee chamfer

Head Diameter:

2.750 inches

Head Height:

Between 0.616 inches and 0.626 inches

Distance From Centerline To Flat:

Between 1.100 inches and 1.110 inches

Shoulder Diameter:

1.998 inches first shoulder and 1.999 inches first shoulder

Shoulder Length:

10.125 inches first shoulder and 10.135 inches first shoulder

Shank Unthreaded Hole Diameter:

0.218 inches first hole

Thread Diameter:

1.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

10.875 inches first hole and 10.885 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium or chromium

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.