

View Online at <https://aerobasegroup.com/nsn/5306-00-437-2670>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.844 inches

**Fastener Length:**

Between 11.094 inches and 11.104 inches

**Head Style:**

Dee chamfer

**Head Diameter:**

2.750 inches

**Head Height:**

Between 0.616 inches and 0.626 inches

**Distance From Centerline To Flat:**

Between 1.100 inches and 1.110 inches

**Shoulder Diameter:**

1.998 inches first shoulder and 1.999 inches first shoulder

**Shoulder Length:**

10.125 inches first shoulder and 10.135 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.218 inches first hole

**Thread Diameter:**

1.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

10.875 inches first hole and 10.885 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium or chromium

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.