

View Online at <https://aerobasegroup.com/nsn/5306-00-437-3572>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

1.031 inches

Head Style:

Hexagon

Head Height:

0.187 inches

Width Between Flats:

0.375 inches

Hole Diameter:

0.062 inches

First Diameter From Head:

Between 0.308 inches and 0.310 inches

Second Diameter From Head:

Between 0.199 inches and 0.201 inches

Third Diameter From Head:

Between 0.308 inches and 0.310 inches

Fourth Diameter From Head:

Between 0.182 inches and 0.187 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.219 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.302 inches and 0.312 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.438 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

0.656 inches

Thread Diameter:

0.250 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Hole Configuration Style:

Hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

4

Material:

Steel

Material Specification:

Qq-s-634, composition 1015 through 1025 federal specification single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232, type m, class 2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.