

View Online at <https://aerobasegroup.com/nsn/5306-00-439-3332>

Thread Class:

1a

Thread Direction:

Right-hand

Thread Length:

0.380 inches

Fastener Length:

Between 3.380 inches and 3.400 inches

Head Style:

Hexagon

Head Height:

Between 0.171 inches and 0.205 inches

Width Between Flats:

Between 0.484 inches and 0.500 inches

First Diameter From Head:

Between 0.325 inches and 0.327 inches

Second Diameter From Head:

Between 0.260 inches and 0.300 inches

Third Diameter From Head:

Between 0.325 inches and 0.327 inches

Fourth Diameter From Head:

Between 0.245 inches and 0.250 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.750 inches and 0.770 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 2.470 inches and 2.500 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 2.980 inches and 2.990 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 3.020 inches and 3.060 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 32.0 rockwell c

Externally Relieved Body Diameter Quantity:

4

Material:

Steel comp 4140

Material Specification:

Sae assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0