

View Online at <https://aerobasegroup.com/nsn/5306-00-440-2122>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.430 inches

Fastener Length:

Between 0.990 inches and 1.030 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.270 inches and 0.280 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.050 inches and 0.060 inches

Hole Diameter:

0.206 inches

Shank Unthreaded Hole Diameter:

0.063 inches first hole

First Diameter From Head:

Between 0.200 inches and 0.205 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.380 inches and 0.390 inches

Thread Diameter:

0.250 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.100 inches first hole

Externally Relieved Body Diameter Quantity:

1

Material:

Steel

Material Specification:

C50t22, fscm 96570 mfr ref single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Ams 2485 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0