

View Online at <https://aerobasegroup.com/nsn/5306-00-440-5745>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.349 inches and 0.416 inches

**Fastener Length:**

Between 1.109 inches and 1.156 inches

**Head Diameter:**

Between 0.303 inches and 0.313 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**First Diameter From Head:**

Between 0.139 inches and 0.149 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.740 inches and 0.760 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.158 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Minimum Yield Strength:**

130000 pounds per square inch

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0