

View Online at <https://aerobasegroup.com/nsn/5306-00-441-1556>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.345 inches

**Fastener Length:**

1.188 inches

**Head Style:**

Dee

**Head Diameter:**

0.625 inches

**Head Height:**

0.093 inches

**Distance From Centerline To Flat:**

0.234 inches

**Shoulder Diameter:**

0.436 inches first shoulder and 0.437 inches first shoulder

**Shoulder Length:**

0.781 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.098 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Qq-c-320 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.