NSN 5306-00-442-6954

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-442-6954

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.535 inches and 0.585 inches
Fastener Length:
Between 1.420 inches and 1.450 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Round
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams6487 assn standard single material response

NSN 5306-00-442-6954 Shear Bolt - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No