## NSN 5306-00-442-7405

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-442-7405 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.437 inches and 0.516 inches **Fastener Length:** Between 1.015 inches and 1.062 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **First Diameter From Head:** Between 0.246 inches and 0.249 inches **Second Diameter From Head:** 0.200 inches **Third Diameter From Head:** Between 0.246 inches and 0.249 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.460 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.580 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.546 inches and 0.578 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5306-00-442-7405

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.