

View Online at <https://aerobasegroup.com/nsn/5306-00-443-5877>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.875 inches and 0.935 inches

**Fastener Length:**

1.750 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.375 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

0.500 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.815 inches and 0.875 inches

**Features Provided:**

Finished head

**Nonstandard Thread Pitch Diameter:**

+0.2797/+0.2824 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Minimum Yield Strength:**

85000 pounds per square inch

**Surface Finish:**

63.0 microinches grip

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5735 assn standard single material response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0