NSN 5306-00-444-6482

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-444-6482

| Thread Class: |
|---------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.781 inches |
| Fastener Length: |
| 1.594 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.265 inches and 0.297 inches |
| Width Between Flats: |
| Between 0.740 inches and 0.752 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| 0.812 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Minimum Yield Strength: |
| 125000 pounds per square inch |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |