NSN 5306-00-445-7358

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-445-7358 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.450 inches **Fastener Length:** Between 6.240 inches and 6.250 inches **Head Style:** Hexagon **Head Height:** Between 0.300 inches and 0.320 inches Width Between Flats: 0.937 inches **First Diameter From Head:** Between 0.623 inches and 0.624 inches **Second Diameter From Head:** Between 0.433 inches and 0.443 inches **Third Diameter From Head:** Between 0.623 inches and 0.624 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.820 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.970 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 5.790 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 3 **Material Specification:** Ams 5735 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5306-00-445-7358

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0