

View Online at <https://aerobasegroup.com/nsn/5306-00-446-3665>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.261 inches and 0.281 inches

**Fastener Length:**

Between 1.350 inches and 1.370 inches

**Head Style:**

Hexagon

**Head Height:**

0.130 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Shoulder Diameter:**

0.3735 inches first shoulder and 0.3745 inches first shoulder

**Shoulder Length:**

0.975 inches first shoulder and 0.995 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.190 inches first hole and 1.210 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0