

View Online at <https://aerobasegroup.com/nsn/5306-00-446-3665>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.261 inches and 0.281 inches

Fastener Length:

Between 1.350 inches and 1.370 inches

Head Style:

Hexagon

Head Height:

0.130 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Shoulder Diameter:

0.3735 inches first shoulder and 0.3745 inches first shoulder

Shoulder Length:

0.975 inches first shoulder and 0.995 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.190 inches first hole and 1.210 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0