

View Online at <https://aerobasegroup.com/nsn/5306-00-446-9304>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.875 inches and 0.935 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.375 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

0.500 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.065 inches and 0.125 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Thread Series Designator:**

Unjf

**Departure From Cited Designator:**

Nne

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0