## NSN 5306-00-446-9304

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-446-9304

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.875 inches and 0.935 inches
Fastener Length:
1.000 inches
Head Style:
Double hexagon w/hole
Head Height:
0.375 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
0.500 inches
Extended Washer Thickness:
Between 0.070 inches and 0.080 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.065 inches and 0.125 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Surface Finish:
63.0 microinches grip
Material:
Steel comp 8740

## **NSN 5306-00-446-9304** Machine Bolt - Page 2 of 2



Material Specification:
Ams 6322 assn standard single material response
Thread Series Designator:
Unjf
Departure From Cited Designator:
Nne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0