

View Online at <https://aerobasegroup.com/nsn/5306-00-451-1138>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.396 inches and 0.416 inches

**Fastener Length:**

Between 2.275 inches and 2.315 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.347 inches and 0.407 inches

**Width Between Flats:**

Between 0.990 inches and 1.010 inches

**Shoulder Diameter:**

0.681 inches first shoulder and 0.683 inches first shoulder

**Shoulder Length:**

1.879 inches first shoulder and 1.899 inches first shoulder

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

185000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232, type z, class 4b military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.