NSN 5306-00-451-5280

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-451-5280

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.506 inches and 0.556 inches |
| Fastener Length: |
| Between 0.766 inches and 0.796 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.254 inches |
| Width Between Flats: |
| Between 0.304 inches and 0.313 inches |
| Extended Washer Diameter: |
| Between 0.465 inches and 0.475 inches |
| Extended Washer Thickness: |
| 0.042 inches |
| Hole Diameter: |
| 0.037 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 260000 pounds per square inch |
| Hardness Rating: |
| 51.0 rockwell c and 54.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams 6485 assn standard single material response, or ams6487 assn standard single material response |

NSN 5306-00-451-5280

Shear Bolt - Page 2 of 2



| Surface Treatment: |
|--------------------|
| Cadmium |

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0