

View Online at <https://aerobasegroup.com/nsn/5306-00-451-8925>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.803 inches and 0.853 inches

Fastener Length:

Between 2.563 inches and 2.593 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.547 inches and 0.567 inches

Width Between Flats:

Between 0.616 inches and 0.627 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.123 inches and 0.143 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0