## NSN 5306-00-451-8925

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-451-8925



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.803 inches and 0.853 inches Fastener Length: Between 2.563 inches and 2.593 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.547 inches and 0.567 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.143 inches Hole Diameter: 0.055 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Thread Diameter:** 0.562 inches Grip Length: Between 1.740 inches and 1.760 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp h11 **Material Specification:** 

Ams 6485 assn standard single material response or ams6487 assn standard single material response

## NSN 5306-00-451-8925

Shear Bolt - Page 2 of 2



Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0