

View Online at <https://aerobasegroup.com/nsn/5306-00-458-8608>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.955 inches and 1.035 inches

**Fastener Length:**

Between 4.470 inches and 4.500 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.795 inches and 0.825 inches

**Width Between Flats:**

Between 1.481 inches and 1.502 inches

**Extended Washer Diameter:**

Between 2.470 inches and 2.510 inches

**Extended Washer Thickness:**

0.120 inches

**Shoulder Diameter:**

2.001 inches

**Shoulder Length:**

Between 3.215 inches and 3.235 inches

**Concentric Hole Diameter:**

1.040 inches

**Thread Diameter:**

1.750 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium head

**Surface Treatment Specification:**

Ds30000 c-2-3 fscm 56878 mfr ref single treatment response threads

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.