

View Online at <https://aerobasegroup.com/nsn/5306-00-461-5684>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.211 inches and 0.261 inches

Fastener Length:

Between 0.533 inches and 0.563 inches

Head Style:

Double hexagon

Head Height:

Between 0.130 inches and 0.150 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.1885 inches and 0.1894 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.405 inches first hole and 0.437 inches first hole

Material:

Steel comp h11 or steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.