
NSN 5306-00-463-0230

Shear Bolt - Page 1 of 2



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.254 inches and 1.274 inches

Fastener Length:

4.264 inches

Head Style:

Double hexagon w/hole

Head Height:

0.808 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Extended Washer Diameter:

Between 1.428 inches and 1.438 inches

Extended Washer Thickness:

0.198 inches

Grip Diameter:

Between 0.8730 inches and 0.8740 inches

Thread Diameter:

0.875 inches

Grip Length:

Between 2.990 inches and 3.010 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:



NSN 5306-00-463-0230

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

