

View Online at <https://aerobasegroup.com/nsn/5306-00-463-0230>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.254 inches and 1.274 inches

**Fastener Length:**

4.264 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.808 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Extended Washer Diameter:**

Between 1.428 inches and 1.438 inches

**Extended Washer Thickness:**

0.198 inches

**Grip Diameter:**

Between 0.8730 inches and 0.8740 inches

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 2.990 inches and 3.010 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0