

View Online at <https://aerobasegroup.com/nsn/5306-00-466-0479>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.586 inches and 0.636 inches

**Fastener Length:**

Between 1.658 inches and 1.688 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.319 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

0.050 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.052 inches and 1.072 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:**

Cadmium or cadmium or cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 type 1 cl 2 military specification 1st treatment response or mil-c-8837 type 2 cl 2 military specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.