## NSN 5306-00-466-0479

Shear Bolt - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5306-00-466-0479 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.586 inches and 0.636 inches **Fastener Length:** Between 1.658 inches and 1.688 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.319 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** 0.050 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams6485 assn standard single material response or ams6487 assn standard single material response **Surface Treatment:** Cadmium or cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 1 cl 2 military specification 1st treatment response or mil-c-8837 type 2 cl 2 military specification 2nd treatment response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5306-00-466-0479

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.