NSN 5306-00-466-9956

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-466-9956

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.500 inches |
| Fastener Length: |
| 4.000 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| 0.618 inches |
| Width Between Flats: |
| Between 0.679 inches and 0.690 inches |
| Extended Washer Diameter: |
| Between 1.040 inches and 1.050 inches |
| Extended Washer Thickness: |
| 0.150 inches |
| Grip Diameter: |
| Between 0.6230 inches and 0.6240 inches |
| Thread Diameter: |
| 0.625 inches |
| Grip Length: |
| 2.500 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hardness Rating: |
| 46.0 rockwell c |
| Material: |
| Steel |
| Material Specification: |
| Ams5844 assn standard single material response |
| Surface Treatment: |
| Passivate and silver |
| Surface Treatment Specification: |
| Qq-p-35, type 1 federal specification 1st treatment response and ams2410 assn standard 2nd treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |

NSN 5306-00-466-9956

Shear Bolt - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0