

View Online at <https://aerobasegroup.com/nsn/5306-00-468-0635>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.595 inches and 0.675 inches

**Fastener Length:**

Between 1.615 inches and 1.635 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.178 inches and 0.198 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.960 inches and 1.020 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.505 inches first hole and 1.525 inches first hole

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0